Power HANDS

















- STURDY
- RELIABLE
- UNTIRING

Other Products:

- ONLINE UPS
- STATIC VOLTAGE
 REGULATORS
- APFC PANELS
- SERVO VOLTAGE
 STABILIZERS
- ISOLATION
 TRANSFORMER



SALIENT FEATURES

- Extended Run time Facility and DG Set Compatible
- Line Interactive / Bi Directional Inverter / Converter module
- Sinewave Output Voltage For compatibility with all types of Load
- Microprocessor Based Design For reliable and efficient performance
- Surge / Spike Protection Prevents electronic equipment and data error/corruption
- RS232 communication interface: Online display of UPS parameters and automatic shutdown in case of extended power failure and thereby prevents data loss
- Boost / Buck Circuit Supports the load even under low voltage conditions without draining the batteries and prevents from damages during over voltages
- Cold Start





Tested by: ETDC & Other Labs

PWM-MOSFET



LINE INTERACTIVE SINE WAVE UPS

TECHNICAL SPECIFICATIONS:

CAPACITY: 600VA, 1000 VA, 1500VA, 2000VA

TOPOLOGY	Line Interactive, Micro Controller Based			
INPUT VOLTAGE RANGE	125-280 Volts			
INPUT FREQUENCY RANGE	50 Hz ± 6%			
OUTPUT IN MAINS MODE	230 VAC +/-8%	OUTPUT IN INVERTER MODE : $230 \pm 3\%$		
PF	0.6	Crest factor	:	3: 1
WAVE FORM	Pure Sine Wave with	Distortion	: less t	than 3% distortion
OUTPUTFREQUENCY RANGE	50 Hz ± 6%			
Efficiency	80%			
CHARGING	I0%oFBatteryAh (I0to12 hrs) Charging Time			
OUTPUT SOCKETS	03 Nos. of indian 3 pin sockets			
PROTECTIONS	Over Load, Battery Low Cut, Over / Under Voltage, Short Circuit			
BATTERY BACKUP	Refer run time chart			
BATTERY TYPE	SMF/Tubular/Auto/Ni-Cad battery			
SWITCH OVER TIME	Less than 5 miliseconds			
INDICATIONS	On mains, On battery, Low battery, UPS trip (Audio/Visual)			
AUDIBLE NOISE	Les than 50 db			
Humidity	95%			

UPS with customised specifications are also available

*All specifications & appearance are subject to change without prior notice due to continuos technology upgradation.



NPS Power Solution Pvt. Ltd. AN ISO-9001 & 14001 COMPANY



C-33, J Park, Mahanagar Extn. Lucknow - 226020 Tele Fax: Desk: (0522)4104163